



Technical Data Sheet:HE3201

Product manual **HE3201** is a modified epoxy acrylate oligomer with the good flexibility, good adhesion, good yellowing and weather resistance and so on.It is especially suitable for all kinds of ink such as screen printing, flexo printing, offset printing, wood coatings, OPV, plastic coatings and metal coatings.

Product features

- Fast curing speed
- Good flexibility
- Good yellowing and weather resistance
- Cost-effective

Recommended use

- Ink: Screen Printing, flexo printing, offset printing
- Plastic coatings
- Wood Coatings
- OPV

Specifications	Functionality (theoretical)	2
	Appearance(By vision)	Clear liquid
	Viscosity (CPS/25℃)	16000-37000
	Color(Gardner)	≤1
	Efficient content(%)	100

Packing Net weight 50KG plastic bucket and net weight 200KG iron drum

Storage conditions Please keep cool or dry place, and avoid sun and heat;
Storage temperature does not exceed 40 °C, storage conditions under normal conditions for at least 6 months.

Use matters

Avoid touching the skin and clothing, wear protective gloves when handling;
Leak with a cloth when the leak, and wash with ethyl acetate;
for details, please refer to the Material Safety Instructions (MSDS);
Each batch of goods to be tested before they can be put into production.